

No.	Change	CM-No.	Done	Date
1.0	LOGO CHANGED		SS	

[3.72in]
94.4mm
Center Pivot
Door Configuration

[1.44in]
36.6mm
Relief

Mounting Screws

Jamb cut out
per site conditions.

[6.89in]
175mm

Minimum screw spacing

[8.66in]
220mm
Recommended

Jamb cut out
per site conditions.

[0.18in]
4.4mm
Seal Relief

[10.00in]
254mm

[5.16in]
131mm
Relief

[12.7mm]
0.50in

[1.18in]
Ø 30mm

(Door Width - jamb clearance + finger guard clearance)

Output End

Service End

[12.7mm]
0.50in

Split line

[3.07in]
78mm
seal relief

Split Line

Split Line

Split Line

SECTION A-A

SECTION B-B

- Center Pivot operator threshold shown. Verify site conditions and compatibility on alternative operator configurations.
- Output seal clearance must be maintained as shown; indicated by "relief" dimensions.
- 1/4" thick thresholds must maintain the 4.4mm[0.16in] seal relief dimension.

Surface treatment		Material		Remark	
		Assembly			
General tolerance		Proj. method	Scale	Drawn	Date
ISO 2768			1:4	BNCMVE	
-		Description			Status
ASSA ABLOY ASSA ABLOY Entrance Systems AB		Threshold Recommendation ASSA ABLOY SW200i-IG			Draft
Rev.	Size	Sheet			
1.0	A3	1 (1)			
Drawing No.					
					1009708

© All rights in and to this material are the sole property of ASSA ABLOY Entrance Systems AB. Copying, scanning, alterations or modifications are expressly forbidden without the prior written consent of ASSA ABLOY Entrance Systems AB.